

**MOLECULAR MODELLING OF SEROTONIN 5-HT_{1A} RECEPTOR
USING AUTOMATED DOCKING OF BIOACTIVE COMPOUNDS
WITH DEFINED GEOMETRY.
NOVEL APPROACH TO GPCR MODELLING**

Marcin Kołaczkowski^a, Mateusz Nowak^b, Maciej Pawłowski^a and Andrzej J. Bojarski^b

^aDepartment of Pharmaceutical Chemistry, Collegium Medicum, Jagiellonian University,
9 Medyczna Street, 30-688 Kraków, POLAND

^bDepartment of Medicinal Chemistry, Institute of Pharmacology, Polish Academy of
Sciences, 12 Smętna Street, 31-343 Kraków, POLAND

Molecular model of serotonin 5-HT_{1A} receptor was constructed by homology modelling (MODELLER 7v7) on the template of bovine rhodopsin X-ray structure. 400 conformations of the receptor were produced and evaluated by automated docking (FlexX) of bioactive, conformationally constrained arylpiperazine derivatives. Such inverse virtual screening was based primarily on the occurrence of interactions between ligand and most important aminoacids (especially Asp^{3.32}) and the interaction energies scored by different scoring functions with consensus scoring (CScore) algorithm. The first step results showed the crucial role of Asp^{3.32} conformation, the most probable binding site and ligand binding mode. The best models were used for docking of wide group of arylpiperazines with different structure and conformational flexibility. Ligand conformation, binding mode and possible interactions with binding site residues were observed and discussed with reference to previous studies in this field.